

# VULCASEAL<sup>®</sup>

## DC139



**VULCASEAL DC139 IS A HEAVY DUTY DEGREASING CLEANER FOR STONE, BRICK AND CONCRETE.**

### PRODUCT DESCRIPTION

---

**Vulcaseal DC139** is a powerful and effective degreasing cleaner.

**Vulcaseal DC139** will remove stubborn greasy stains and soiling caused by atmospheric and industrial pollution.

**Vulcaseal DC139** is formulated with biodegradable components.

**Vulcaseal DC139** is particularly suitable for horizontal substrates (floors, paved ground surfaces) and can be used on various indoor and outdoor surfaces (concrete, cement, natural and artificial stone, terracotta, tiling, stoneware, marble, etc).

**Vulcaseal DC139** does not alter the appearance or aesthetics of surfaces being treated (always test a small area first).

### CHEMICAL COMPOSITION

---

Vulcaseal DC139 is a blend of surface active chemicals.

### CHARACTERISTICS

---

**Non-corrosive to most surfaces (when diluted) do not use neat on aluminium**

**Biodegradable**

**Easy to use**

**Water-borne product**

**Does not alter the treated surface**

**Particularly suitable for horizontal surfaces**

# VULCASEAL®

## DC139



### PACKAGING

1 and 5 litre containers.

### TECHNICAL DATA

Physical State at 20 °C	Liquid
Appearance	Pale Yellow
Odour	Mild characteristic odour
pH	13 ± 0.5
Boiling point [°C]	100 °C
Density	1.06 Kg/L
Solubility in water [vol/vol]	Fully soluble
Flash Point	N/A
VOC	80 g/l

### COVERAGE PER LITRE

The figures indicated are approximate and should be used only as a general guideline: **1 Litre = 5 to 15m<sup>2</sup>.**

### STORAGE

24 months from the date of manufacture in original unopened container in a clean, dry area. Do not store below 5°C.

### CLEANING EQUIPMENT

Clean tools and equipment immediately after use with water.

### APPLICATION

Always test on a small hidden portion of the substrate before applying.

Vulcaseal DC139 can be used neat on heavy contamination or can be diluted by adding 1 part product with up to 20 parts water depending on the staining to be removed:

Heavily contaminated greasy surfaces eg.

Garage workshops - use neat

Kitchen floors - 1 to 5-10 parts water

Use a low pressure hand spray unit or brush. Apply the product liberally and allow the product to act for:

1-2 minutes for lightly soiled surfaces

5-10 minutes for heavily soiled surfaces

For removing deep penetrating lubricating oil and stains, it may be necessary to apply the product twice allowing 10 mins between applications.

Whilst the surface is still wet, thoroughly rinse with a high pressure water jet at 80-100 bar.

For optimum results use hot water at around 80°C, and vacuum up using a wet & dry vacuum.

Treated substrates may not need to be neutralized (test).

To prevent future soiling, it is recommended to use a suitable protection treatment.

Important: The contents of this document are the result of our experience with this product. We cannot be in any way held liable for its use in individual cases.

**For more information, please see the Material Safety Data Sheet.**

### RECOMMENDATIONS

Do not apply during rain, frost, or when surface and air temp is <5°C and >30°C.

Do not dilute or mix with any other product.