

# SAFETY DATA SHEET UltraTileFix ProGrout Flexible Bahama Beige

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name UltraTileFix ProGrout Flexible Bahama Beige

1.2. Relevant identified uses of the substance or mixture and uses advised against

**Uses advised against**No specific uses advised against are identified.

1.3. Details of the supplier of the safety data sheet

**Supplier** Instarmac Group plc

Danny Morson Way

Birch Coppice Business Park

Dordon, Tamworth Staffordshire. B78 1SE United Kingdom

Tel: +44 (0) 1827 872244 Fax: +44 (0) 1827 874466

email@instarmac.co.uk www.instarmac.co.uk

1.4. Emergency telephone number

**Emergency telephone** +44(0)1827 254433 +44 (0)7971 217 347 (24 hours)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

**Health hazards** Eye Dam. 1 - H318

**Environmental hazards** Aquatic Chronic 3 - H412

**Human health** See Section 11 for additional information on health hazards.

**Environmental** The product is not expected to be hazardous to the environment.

2.2. Label elements

**Pictogram** 



Signal word Danger

Hazard statements H318 Causes serious eye damage.

H412 Harmful to aquatic life with long lasting effects.

# UltraTileFix ProGrout Flexible Bahama Beige

**Precautionary statements** P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P310 Immediately call a POISON CENTER/ doctor.

P501 Dispose of contents/ container in accordance with national regulations.

Contains Hexacalcium hexaoxotris[sulphato(2-)]dialuminate(12-)

Supplementary precautionary statements

Supplementary precautionary P310 Immediately call a POISON CENTER/ doctor.

#### 2.3. Other hazards

This substance is not classified as PBT or vPvB according to current EU criteria.

## SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Classification according to EC 1272/2008 (CLP)

#### 3.2. Mixtures

Natural Calcium Carbonate 60-100%

CAS number: 1317-65-3

Classification
Not Classified

#### Hexacalcium hexaoxotris[sulphato(2-)]dialuminate(12-)

10-30%

**Classification** Eye Dam. 1 - H318

Quartz <1%

**Classification**Not Classified

## POLYVINYL ALCOHOL AND SILANE

<1%

CAS number: -

## Classification

Not Classified

#### SHADECRETE CARDINAL RED

<1%

CAS number: —

#### Classification

Not Classified

# UltraTileFix ProGrout Flexible Bahama Beige

2-OCTYL-2H-ISOTHIAZOL-3-ONE <1%

#### Classification

Acute Tox. 4 - H302 Acute Tox. 3 - H311 Acute Tox. 3 - H331 Skin Corr. 1B - H314 Eye Dam. 1 - H318 Skin Sens. 1 - H317 Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410

The full text for all hazard statements is displayed in Section 16.

#### SECTION 4: First aid measures

## 4.1. Description of first aid measures

General information Remove affected person from source of contamination. Get medical attention if any discomfort

continues.

**Inhalation** Move affected person to fresh air and keep warm and at rest in a position comfortable for

breathing. Get medical attention if any discomfort continues.

Ingestion Rinse mouth thoroughly with water. Give plenty of water to drink. Keep affected person under

observation. Get medical attention if any discomfort continues. Show this Safety Data Sheet

to the medical personnel. Never give anything by mouth to an unconscious person.

Skin contact Rinse immediately with plenty of water. Remove contaminated clothing. Get medical attention

if any discomfort continues.

Eye contact Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide

apart. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort

continues.

## 4.2. Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations.

## SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media Use fire-extinguishing media suitable for the surrounding fire.

## 5.2. Special hazards arising from the substance or mixture

**Specific hazards** Not known. No unusual fire or explosion hazards noted.

Hazardous combustion

products

Does not decompose when used and stored as recommended.

#### 5.3. Advice for firefighters

Revision date: 31/01/2018

# UltraTileFix ProGrout Flexible Bahama Beige

Protective actions during

firefighting

No specific firefighting precautions known.

Special protective equipment

Use protective equipment appropriate for surrounding materials.

for firefighters

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

#### 6.2. Environmental precautions

**Environmental precautions** Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up** GENERAL. For waste disposal, see Section 13.

#### 6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. Collect and dispose of spillage as indicated in Section

13. See Section 11 for additional information on health hazards.

## SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

**Usage precautions** No specific recommendations.

## 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions** Store at moderate temperatures in dry, well ventilated area.

Storage class Unspecified storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

## SECTION 8: Exposure Controls/personal protection

#### 8.1. Control parameters

#### Occupational exposure limits

#### **Natural Calcium Carbonate**

Long-term exposure limit (8-hour TWA): 4 mg/m³

#### Quartz

Long-term exposure limit (8-hour TWA): WEL 0.3 mg/m<sup>3</sup>

## POLYVINYL ALCOHOL AND SILANE

Long-term exposure limit (8-hour TWA): 4 mg/m³

#### SHADECRETE CARDINAL RED

Long-term exposure limit (8-hour TWA): 10.00 mg/m³ Short-term exposure limit (15-minute): 4.00 mg/m³

WEL = Workplace Exposure Limit

Ingredient comments No exposure limits known for ingredient(s).

#### 8.2. Exposure controls

Revision date: 31/01/2018

# UltraTileFix ProGrout Flexible Bahama Beige

#### Protective equipment







Appropriate engineering controls

Not relevant.

Eye/face protection

The following protection should be worn: Chemical splash goggles.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if

a risk assessment indicates skin contact is possible.

Other skin and body

protection

Wear appropriate clothing to prevent any possibility of skin contact.

Hygiene measures Wash at the end of each work shift and before eating, smoking and using the toilet. No

specific hygiene procedures recommended but good personal hygiene practices should

always be observed when working with chemical products.

Respiratory protection No specific recommendations. Respiratory protection may be required if excessive airborne

contamination occurs.

#### SECTION 9: Physical and Chemical Properties

## 9.1. Information on basic physical and chemical properties

**Appearance** Dusty powder.

9.2. Other information

Other information Not available.

## SECTION 10: Stability and reactivity

#### 10.1. Reactivity

**Reactivity** There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability No particular stability concerns.

#### 10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

Not applicable. No potentially hazardous reactions known.

# 10.4. Conditions to avoid

Conditions to avoid There are no known conditions that are likely to result in a hazardous situation.

10.5. Incompatible materials

Materials to avoid No specific material or group of materials is likely to react with the product to produce a

hazardous situation.

## 10.6. Hazardous decomposition products

Hazardous decomposition

Does not decompose when used and stored as recommended.

products

#### SECTION 11: Toxicological information

# 11.1. Information on toxicological effects

**Toxicological effects** No information available.

Revision date: 31/01/2018

# UltraTileFix ProGrout Flexible Bahama Beige

**General information** No specific health hazards known.

**Inhalation** No specific health hazards known.

Ingestion May cause irritation. Symptoms following overexposure may include the following: Stomach

pain. Nausea, vomiting. Diarrhoea.

**Skin contact** Irritating to skin.

**Eye contact** Irritating to eyes.

Acute and chronic health

hazards

This product may cause skin and eye irritation.

## SECTION 12: Ecological Information

**Ecotoxicity** There are no data on the ecotoxicity of this product.

12.1. Toxicity

**Toxicity** No information available

#### 12.2. Persistence and degradability

Persistence and degradability No information available There are no data on the degradability of this product.

#### 12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

12.4. Mobility in soil

**Mobility** The product is non-volatile.

#### 12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

assessment

This substance is not classified as PBT or vPvB according to current EU criteria.

## 12.6. Other adverse effects

Other adverse effects Not available.

#### **SECTION 13: Disposal considerations**

## 13.1. Waste treatment methods

**General information** When handling waste, the safety precautions applying to handling of the product should be

considered.

**Disposal methods**Dispose of waste to licensed waste disposal site in accordance with the requirements of the

local Waste Disposal Authority.

#### SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods

(IMDG, IATA, ADR/RID).

#### 14.1. UN number

Not applicable.

## 14.2. UN proper shipping name

Not applicable.

# UltraTileFix ProGrout Flexible Bahama Beige

#### 14.3. Transport hazard class(es)

Not applicable.

## 14.4. Packing group

Not applicable.

#### 14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

## 14.6. Special precautions for user

Not applicable.

## 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

#### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations Health and Safety at Work etc. Act 1974 (as amended).

Control of Substances Hazardous to Health Regulations 2002 (as amended).

**Guidance** Safety Data Sheets for Substances and Preparations.

#### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

#### SECTION 16: Other information

General information Only trained personnel should use this material.

**Issued by** HS&E Manager.

Revision date 31/01/2018 SDS status Approved.

Hazard statements in full H302 Harmful if swallowed.

H311 Toxic in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H331 Toxic if inhaled.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.